

Standalone Antenna
Reflection Tester



Features

- LCD Display works in direct sunlight and with backlight in dark areas.
- Built-in synthesized RF sweeping source.
- Measured results can be stored for further analysing and documentation on internal and external storage media
- Time stamp and operator ID is possible
- All in one analysing for antenna tuning and verify
- FAT 2710 measures antenna, frequency, SWR and bandwidth by sweeping band of interest
- A cost-effective SWR Analyzer covering all major Cellular and mobile radio communication bands
- FAT 2710 gives you quick and reliable trouble-shooting
- 30 - 2700 MHz

A Breakthrough in SWR analysing

Specifications

Model	FAT 2710
Application	Measurement of SWR in 50 Ω transmission lines
Frequency range	30->2700 MHz entered as centre and span
Center Frequency	30 to 2700 MHz.
Span	0 to 2670 MHz.
Frequency stability	±50ppm
Measurement range	1.0<SWR<9.9, 0<dB<-30dB
Impedance	Nom. 50 Ω
Generator output	Approx. -8dBm
Max. input on test terminal	100 mW
Tolerance on SWR reading	30-650MHz ± 10%; 650-1450MHz ± 10%; and 1450-2700MHz ±15%
Operating temperature range	0° C-> + 50° C
Storage temperature range	-30° C -> + 50° C
Connectors	“N”-female RF test connector. USB A type for memory key. USB B type for serial PC communication. Mini DIN for RS232 communication up to 38400 Baud
Power supply	4 NiMH type AA rechargeable batteries (Batteries, NiMH rechargeable and 230VAC/7.5VDC charger supplied)
Auto Power off (no failure!)	For battery economy, FAT 2710 automatically turns off 3 min. after last entry
Normal operating use	Fully charged: More than 10 hours.
Colour	Silver/blue
Width	82 mm
Depth	31 mm
Height	165 mm
Weight	500 gram (incl. Batteries)
EMC	Complies with directive 89/336EEC as amended by 92/31EEC and 93/68/EEC
Standards	Emissions: EN 61000-6-4: 2001 Immunity: EN 61000-6-2: 2005
Accessory	Soft carrying bag with RF-adaptor set, car charging cable

Order Number:
Order Number for Accessory:

BN: 80008282
BN: 50008286